



→ THE NO NONSENSE PLY •





Marine Blue is a boiling waterproof veneer crafted from 100% tropical wood with a face veneer thickness of 0.30mm, making it suitable for indoor and outdoor furniture. This grade is the perfect blend of durability and quality for all your furniture needs.

TECHNICAL SPECIFICATION

| Thickness in mm | 4 | 6 | 9 | 12 | 16 | 19 | 25 | |
|---|------------|---|---|----|----|----|----|--|
| Number of Plies | 5 | 5 | 7 | 9 | 11 | 13 | 17 | |
| Fire Safety | Yes | | | | | | | |
| Veneer Treatment | preser | Each veneer is treated with preservative before pressing through Vacuum Pressure Technology | | | | | | |
| Density approx. in kg per CBM | 700 | 700 | | | | | | |
| Impact Resistance | High s | High strength & dimensional stability | | | | | | |
| Screw Holding Strength (kg) | ≥250 | ≥250 | | | | | | |
| Nail Holding Strength (kg) | ≥105 | ≥105 | | | | | | |
| Quad-Core Press | Yes | Yes | | | | | | |
| Adhesives of Plies Glue Shear Strength (N) Visual Inspection | | ≥1620 Excellent | | | | | | |
| 100% Composed Veneer | * | All layers are pre-composed in an automatic state-of-the-art machine | | | | | | |
| Moisture Content (%) | 8 -12 | 8 -12 | | | | | | |
| Specific Gravity (g/cc) | ≥0.70 | ≥0.70 | | | | | | |
| Water Absorption (%) | <5 | <5 | | | | | | |
| Static Bending Strength (N/mm2) | | | | | | | | |
| Modulus of Rupture (MOR): Along the grain Across the grain | ≥55 ≥40 | | | | | | | |
| Modulus of Elasticity (MOE): Along the grain Across the grain | | ≥8000 ≥4800 | | | | | | |
| Adhesive | Phenol | Phenolic adhesive | | | | | | |
| Emission Norms | Bonde | Bonded with E1 certified resin | | | | | | |
| Calibration | 100% | 100% as per Precision Calibration Technology | | | | | | |
| | | | | | | | | |